



A Division of First Citizens Bank

GP15D specifications



Builder Model	<ul style="list-style-type: none"> • EMD GP15D
Nominal Dimensions	<ul style="list-style-type: none"> • Length Between Couplers: 57' 2" • Distance Between Bolster Centers: 40' 00" • Height - Cab Roof to Top of Rail: 15' 1" • Truck Wheel Base: 9' 00"
Main Components	<ul style="list-style-type: none"> • Caterpillar 3512 Prime Mover • Kato 8PG Main Generator • 26L Airbrake
Drive	<ul style="list-style-type: none"> • Traction Motors: 4 • Model: D78 • Gear Ratio: 62:15 • Wheel Diameter: 41"
Weights and Capacities	<ul style="list-style-type: none"> • Nominal Weight: 256,000 lbs • Fuel Tank Capacity: 2,300 gals • Sand: 45 cu ft • Cooling Water: 135 gals • Lubricating Oil: 219 gals
Performance	<ul style="list-style-type: none"> • Minimum Continuous Speed: 8.2 mph • Continuous Tractive Effort: 55,000 lbs • Starting Tractive Effort: 86,000 lbs • Maximum Locomotive Speed: 70 mph
Horsepower	<ul style="list-style-type: none"> • Engine Speed: 1,800 rpm • Tractive Horsepower: 1,500
Build Date	<ul style="list-style-type: none"> • 2001
Additional Equipment	<ul style="list-style-type: none"> • Air Conditioning • AESS • Ditch lights front and rear • Slow speed control

citrail.com

