



A Division of First Citizens Bank



# GP20D specifications

<b>Builder Model</b>	<ul style="list-style-type: none"> <li>• EMD GP20D</li> </ul>
<b>Nominal Dimensions</b>	<ul style="list-style-type: none"> <li>• Length Between Couplers: 57' 2"</li> <li>• Distance Between Bolster Centers: 40' 00"</li> <li>• Height - Cab Roof to Top of Rail: 15' 1"</li> <li>• Truck Wheel Base: 9' 00"</li> </ul>
<b>Main Components</b>	<ul style="list-style-type: none"> <li>• Caterpillar 3516 Prime Mover</li> <li>• Kato 8P6 Main Generator</li> <li>• 26L Airbrake</li> </ul>
<b>Drive</b>	<ul style="list-style-type: none"> <li>• Traction Motors: 4</li> <li>• Model: D87</li> <li>• Gear Ratio: 70:17</li> <li>• Wheel Diameter: 41"</li> </ul>
<b>Weights and Capacities</b>	<ul style="list-style-type: none"> <li>• Nominal Weight: 260,000 lbs</li> <li>• Fuel Tank Capacity: 2,300 gals</li> <li>• Sand: 45 cu ft</li> <li>• Cooling Water: 135 gals</li> <li>• Lubricating Oil: 219 gals</li> </ul>
<b>Performance</b>	<ul style="list-style-type: none"> <li>• Minimum Continuous Speed: 9.3 mph</li> <li>• Continuous Tractive Effort: 65,000 lbs</li> <li>• Starting Tractive Effort: 97,000 lbs</li> <li>• Maximum Locomotive Speed: 70 mph</li> </ul>
<b>Horsepower</b>	<ul style="list-style-type: none"> <li>• Engine Speed: 1,800 rpm</li> <li>• Tractive Horsepower: 2,000</li> </ul>
<b>Build Date</b>	<ul style="list-style-type: none"> <li>• 2001</li> </ul>
<b>Additional Equipment</b>	<ul style="list-style-type: none"> <li>• Air Conditioning</li> <li>• AESS</li> <li>• Ditch lights front and rear</li> <li>• Extended Range Dynamic Brakes</li> <li>• Slow speed control</li> </ul>

[citrail.com](http://citrail.com)

