



A Division of First Citizens Bank

AC4400CW specifications



Builder Model	<ul style="list-style-type: none"> • General Electric AC4400CW
Nominal Dimensions	<ul style="list-style-type: none"> • Length Between Couplers: 73' 2" • Distance Between Bolster Centers: 50' 4" • Height - Cab Roof to Top of Rail: 15' 6" • Truck Wheel Base: 13' 2"
Main Components	<ul style="list-style-type: none"> • 7FDL16 Prime Mover • GMG192 Main Traction Alternator • Wabtec FastBrake Airbrake
Drive	<ul style="list-style-type: none"> • Traction Motors: 6 • Model: GEB13 • Gear Ratio: 83:20 • Wheel Diameter: 42"
Weights and Capacities	<ul style="list-style-type: none"> • Nominal Weight: 426,000 lbs • Fuel Tank Capacity: 5,000 gals • Sand: 40 cu ft • Cooling Water: 380 gals • Lubricating Oil: 410 gals
Performance	<ul style="list-style-type: none"> • Minimum Continuous Speed: 13.7 mph • Continuous Tractive Effort: 145,000 lbs • Starting Tractive Effort: 180,000 lbs • Maximum Locomotive Speed: 70 mph
Horsepower	<ul style="list-style-type: none"> • Engine Speed: 1,050 rpm • Tractive Horsepower: 4,400
Build Date	<ul style="list-style-type: none"> • 2004
Additional Equipment	<ul style="list-style-type: none"> • Air Conditioning • AESS • Ditch lights front and rear • Distributed power • Toilet

citrail.com

